

Digital Printing Media of SFC gives you significantly short drying time and brilliant & true color reproduction, which are essential for displays, light box and signs, etc.
SFC Digital printing Media also provides you perfect waterproof and durability.

UV-220D Block Out Banner

Technical information

■ Specification

Total Thickness	220 ± 10 μm
Weight	165 ~ 175 g/m ²
Specific gravity	0.75
Base Materials	Special PP Synthetic Paper
Surface	Matt
Ink Application	UV & LATEX INK
Standard Length	50, 100, 300 M
Standard Width	36" - 60"
Standard Core	3"
Adhesive	None
Water Resistance	Excellent

■ Technical Data

Media Color	L : 66.39 a : 1.48 b : 0.59
Whiteness / Yellowness	37.94 / -1.45
Light Transmittance	-
Tensile Strength	MD : ≥ 140 MPa / TD : ≥ 30 Mpa
Tear Strength	MD : ≥ 135 Mpa / TD : ≥ 20 Mpa
Elongation at break	MD : ≥ 5% / TD : ≥ 2%

Applications

1. Specialized photo printing
2. Window display
3. POP Ad.

Guidelines of Handling & Storage conditions

1. Suitable printing condition : 18 ~ 25°C temperature, 30 ~ 50 % humidity recommend.
2. To avoid defect on material - like fingerprints - use of cotton gloves is recommend.
3. Too high temperature of pre-heating or strong dryer may lead to an inferior print and color difference.
4. Ambient temperature and weather can affect the condition of products.
5. Recommend to leave the materials away from dust & direct sunlight.
6. After use, storage is best to be done in the original case.



Equipos y Materiales para Impresión Digital de Gran Formato

Tel. 01 (55) 5617 2599 / 01 800 71 85 600

www.sagaró.com.mx

contacto@sagaró.com.mx

Sucursales: CDMX Sur, CDMX Centro, Tlalnepantla EdoMex, Puebla, Monterrey, Guadalajara, Torreón, Querétaro, León, Veracruz, Mérida.