Digital Printing Media Creating & Innovating of Digital Printing Media

Digital Printing Media of SFC gives you significantly short drying time and brilliant & true color reproduction, which are essential for displays, light box and signs, etc. Digital printing Media also provides you perfect waterproof and durability.

SC-310 EASY BANNER

Techinical information

Speccification

Total Weight	170 ~ 200 g/m²
Base Materials	Non-woven fabric 100g
Surface	Matt
Ink Application	UV & Latex inks
Standard Length	30M-500M
Standard Width	36"- 60"
Standard Core	3" & 6"
Adhesive	None
Water Resistance	Very Good

■ Technical Data

Media Color	L:52.22 a:0.77 b:4.86
Whiteness / Yellowness	11.13 / 11.41
Light Transmittance	20.34 (@ 400 ~ 700nm)
Tensile Strength	MD : ≥ 15 MPa / TD : ≥ 20 Mpa
Tear Strength	MD : ≥ 5 Mpa / TD : ≥ 10 Mpa
Elongation at break	MD : ≥ 30% / TD : ≥ 25%
Dimensional Stability	MD : ≤ 1% / TD : ≤ 1%
	(@ 150°C, 30min)

Applications

- 1. X banner, Y banner, I banner
- 2. POP advertising indoor & outdoor
- 3. The bus and subway shelter
- 4. indoor & outdoor advertising display

Guidelines of Handling & Storage conditions

- 1. Suitable printing condition : 18 ~ 25°C temperature, 30 ~ 50 % humidity recommend.
- 2. To avoid defect on material like fingerprints use of cotton gloves is recommend.
- 3. Too high temperature of pre-heating or strong dryer may lead to an inferior print and color difference.
- 4. Ambient temperature and weather can affect the condition of products.
- 5. Recommend to leave the materials away from dust & direct sunlight.
- 6. After use, storage is best to be done in the original case.



Equipos y Materiales para Impresión Digital de Gran Formato Tel. 01 (55) 5617 2599 / 01 800 71 85 600

www.sagaro.com.mx

contacto@sagaro.com.mx

Sucursales: CDMX Sur, CDMX Centro, Tlalnepantla EdoMex, Puebla, Monterrey, Guadalajara, Torreón, Querétaro, León, Veracruz, Mérida.