

Product Bulletin

GF 111 Dry Erase Film Permanent Adhesive



GF 111 is a 2-mil clear film coated with a permanent acrylic pressure sensitive adhesive on a smooth paper liner designed for use with dry erase markers.

Applications

This product is recommended for producing general purpose graphics, decals and unprinted substrates for use with dry erase pens. Typical substrates are paper, cardboard, photos and unprinted substrates. If producing industrial grade dry erase boards or multi layer laminates of either plastics or metal consult with your Concept sales representative. These include sign in boards typically found in hospitals, retail establishments and restaurants.

For best results, we suggest the following dry erase brand marking pens: Avery Marks-a-lot® (chisel point), Expo Scents® (chisel point), Expo Bold color® (chisel Point), Expo regular® (chisel point) brand marking pens.

Thickness

Film 2.0 mils.
Adhesive 0.8 to 1.0 mils.
Liner 4.0 mils.
(Thickness variance +/- 10%)

Dimensional Stability

Film can react to heat in processing. In laminating process do not use excessive unwind tension or nip roll pressure as curl could result.

Temperature Ranges

Minimum application temperature +40°F.
Service temperature is -40°F to +200°F.

Expected Exterior Life

Limited.
Dry Erase Film has limited resistance to UV exposure.
Test fully for any extended outdoor use.

Adhesion

To stainless steel 48 oz/in.
PSTC-1 with 24-hour dwell at 70°F and 50% relative humidity.
Typical values. Individual values may vary. Test thoroughly before production.

Water Resistance Humidity Resistance Storage Stability

Good. Immersion not recommended.
Good
1-year shelf life when stored at 70°F and 50% relative humidity.

Product Code

GF 111-54



Equipos y Materiales para Impresión Digital de Gran Formato

Tel. 01 (55) 5617 2599 / 01 800 71 85 600

www.sagaró.com.mx

contacto@sagaró.com.mx

Sucursales: CDMX Sur, CDMX Centro, Tlalnepantla EdoMex, Puebla, Monterrey, Guadalajara, Torreón, Querétaro, León, Veracruz, Mérida.